KET-RKE-032



APPLICATIONS
Data Centres and racks

KET-RKE-063

VERSIONS KET-RKE-063.P32S32





Industrial extension cord 32 A with ModBUS single-phase power meter

- Integrated Power Meter
- Supports loads up to 32 A
- Extension length of 3 m
- RS485 ModBUS Output

KET-RKE-032 is an industrial extension cord with an integrated single-phase current meter that supports loads up to 32

It is equipped with an RS485 port to connect to other KET-RKE series in daisy-chain (with KET-RKY-101 accessory cable) and to the Rack Monitor KET-RKS or KET-RKM (with KET-RKY-100 accessory cable).

The extension has a total length of 3 m and has a three-pole connector (phase, neutral, ground) that sports 230 VAC @

TECHNICAL FEATURES		
GENERAL SPECIFICATIONS	Protection Range: Case: IP56; Socket: IP67 Operative Temperature: -25 ÷ +55 °C Storage Temperature: -40 ÷ +70 °C Relative Humidity: MAX 95% not condensing	
CASE	Dimensions: 160 x 115 x 85 mm (W x H x D) Mounting: Wall Material: Thermoplastics	
POWER SUPPLY	Supply Voltage: Self power, 230 VAC (50 Hz) Consumption: <10 VA Connectors types: Industrial extension of 3 m (5 x 6 mm²) with 3-pin connectors (phase, neutral and ground)	
RS485 INTERFACE	Supported Protocols: ModBUS RTU Communication Rate: 38400, 19200, 9600, 4800 bps Isolation: Class II Connectors types: 1 RJ45 for connection to other extensions and 1 RJ45 for connection to the rack	
CURRENT AND VOLTAGE INPUT	Voltage Inputs: 230 VAC Current Inputs: 32 A @ 50 Hz	
CERTIFICATIONS	Referends Standard: EN50470, IEC61000, EN55022, IEC60068, IEC60529, IEC60695-2-11 Approvals: CE, MID Security: Metrology:	

