



KET-DIM-100.NR

Applications

Smart City

unresinated wireless control module with 0-10V output

- Device control with 0-10 V input
- Designed for road applications
- Integrated repeater function
- Extended radio range

KET-DIM-100.NR is a wireless analog control module designed for the remote control of various devices, including lamps, pumps, and motors, equipped with a 0-10 V?regulation input. Its wireless nature simplifies installation and offers flexible device management. Its compact dimensions make it ideal for integration within lighting equipment such as ceiling lights and street lamps. It features an IP40 protection rating without internal resin coating. Thanks to the integrated repeater function and the amplified radio, the KET-DIM-100.NR facilitates the simple and cost-effective expansion of the X-Monitor network, leveraging IEEE 802.15.4 wireless communication technology.

Technical Features	
General specifications	Protection Range: IP40 Operative Temperature: -15 ÷ +70 °C Storage Temperature: Relative Humidity:
General specifications	Protection Range: IP40 Operative Temperature: -15 ÷ +70 °C Storage Temperature: Relative Humidity: Dimensions: 100 x 45 x 30 mm (W x H x D) Mounting: Wall mounting Material: Black nylon
General specifications	Protection Range: IP40 Operative Temperature: -15 ÷ +70 °C Storage Temperature: Relative Humidity: Dimensions: 100 x 45 x 30 mm (W x H x D) Mounting: Wall mounting Material: Black nylon Supply Voltage: 230 VAC with integrated power supply (50-60 Hz) Consumption: 1.5 VA Connectors types: Device supplied with pre-skinned cable terminals
General specifications	Protection Range: IP40 Operative Temperature: -15 ÷ +70 °C Storage Temperature: Relative Humidity: Dimensions: 100 x 45 x 30 mm (W x H x D) Mounting: Wall mounting Material: Black nylon Supply Voltage: 230 VAC with integrated power supply (50-60 Hz) Consumption: 1.5 VA Connectors types: Device supplied with pre-skinned cable terminals Channels: 1 Digital Inputs: For clean contact with control, alarm, pulse countersecond counter, etc. functions.
General specifications	Protection Range: IP40 Operative Temperature: -15 ÷ +70 °C Storage Temperature: Relative Humidity: Dimensions: 100 x 45 x 30 mm (W x H x D) Mounting: Wall mounting Material: Black nylon Supply Voltage: 230 VAC with integrated power supply (50-60 Hz) Consumption: 1.5 VA Connectors types: Device supplied with pre-skinned cable terminals Channels: 1 Digital Inputs: For clean contact with control, alarm, pulse counters second counter, etc. functions. Output Type: Remote control of devices with a 0-10 V control input