



Applications

Air Quality



Wireless infrared remote control for controlling air conditioners and heat pumps

- Large library of supported devices
- IR receiver for acquisition of custom commands
- Supports multiple devices simultaneously
- Perfect integration into BMS / BEMS systems

KET-WIR-100 is an **infrared remote control** capable of controlling a wide range of air conditioners and heat pump systems. Using KET-WIR-100 it becomes simple to integrate cooling or heating elements in building energy management systems (BMS / BEMS).

Management can be direct or intermediated by the supervision system.

Suitable for use in public environments supports keyboard lock and limitation of active functions.

Technical Features	
General specifications	Protection Range: IP40 Operative Temperature: -10 ÷ +60 °C Storage Temperature: -20 ÷ +70 °C Relative Humidity: MAX 85% not condensing
General specifications	Protection Range: IP40 Operative Temperature: -10 ÷ +60 °C Storage Temperature: -20 ÷ +70 °C Relative Humidity: MAX 85% not condensing Dimensions: 100 x 100 x 22.5 mm (W x H x D) Mounting: Panel mounting with supplied supports Material: ABS, self extinguishing: UL 94 V-O
General specifications	Protection Range: IP40 Operative Temperature: -10 ÷ +60 °C Storage Temperature: -20 ÷ +70 °C Relative Humidity: MAX 85% not condensing Dimensions: 100 x 100 x 22.5 mm (W x H x D) Mounting: Panel mounting with supplied supports Material: ABS, self extinguishing: UL 94 V-O Supply Voltage: 5 ÷ 12 VDC Consumption: Connectors types: Removable spring clamps
General specifications	Protection Range: IP40 Operative Temperature: -10 ÷ +60 °C Storage Temperature: -20 ÷ +70 °C Relative Humidity: MAX 85% not condensing Dimensions: 100 x 100 x 22.5 mm (W x H x D) Mounting: Panel mounting with supplied supports Material: ABS, self extinguishing: UL 94 V-O Supply Voltage: 5 ÷ 12 VDC Consumption: Connectors types: Removable spring clamps Max distance: 3 m Learning mode: Supported Supported devices: Available on web site (use QR Code for quick access)
General specifications	Protection Range: IP40 Operative Temperature: -10 ÷ +60 °C Storage Temperature: -20 ÷ +70 °C Relative Humidity: MAX 85% not condensing Dimensions: 100 x 100 x 22.5 mm (W x H x D) Mounting: Panel mounting with supplied supports Material: ABS, self extinguishing: UL 94 V-O Supply Voltage: 5 ÷ 12 VDC Consumption: Connectors types: Removable spring clamps Max distance: 3 m Learning mode: Supported Supported devices: Available on web site (use QR Code for quick access) Channels: 1 for drycontact Digital Inputs:
General specifications	Protection Range: IP40 Operative Temperature: -10 ÷ +60 °C Storage Temperature: -20 ÷ +70 °C Relative Humidity: MAX 85% not condensing Dimensions: 100 x 100 x 22.5 mm (W x H x D) Mounting: Panel mounting with supplied supports Material: ABS, self extinguishing: UL 94 V-O Supply Voltage: 5 ÷ 12 VDC Consumption: Connectors types: Removable spring clamps Max distance: 3 m Learning mode: Supported Supported devices: Available on web site (use QR Code for quick access) Channels: 1 for drycontact Digital Inputs: Supported Protocols: X-Monitor Protocol (X-MP) / IEEE 802.15.4 Radio Frequency: 2.4 GHz Output Power: +20 dBm Sensitivity: -101 dBm Antenna Type: Internal Max Distance (Free Air): Over 600 m